



HIDROMAS
GALİPOĞLU®

Phone : 90.332 239 08 52 (pbx)

Fax : 90.332 239 08 51

Mail : hidromas@hidromas.com

Address : Büyükkayacık Mah. Konya O.S.B. 3 Nolu Sk No:1/A 42250

SELÇUKLU / KONYA

TÜRKİYE



GHS 135-4-4440 C TEL.SİL.

Product Code :

43135444403

Reference No :

01-001



A :	155
B :	60
C :	193
D :	60
E :	350
F :	
G :	
H :	94
I :	
J :	
K :	
L :	1402
*L :	1432
M :	
N :	
O :	
P :	
R :	
S :	42
S1 :	
T :	
U :	
V :	
W :	
Y :	
Z :	

EFFECTIVE DIAMETER (mm)						135	116	98	80		
STROKE (mm)						1110	1110	1110	1110		
THRUST AT 170 BAR (TONS)						24.1	17.8	12.7	8.5		

All sizes were given as mm

SPECIFICATIONS

- Stroke : 4440
- *Inc 30 mm pull out : Tolerance +20 ; 0
- Working pressure : 170 Bar
- Max. working pressure : 190 Bar
- Working Temperature : -23 °C / +80 °C
- Total Volume : 50.4 L
- Weight Cylinder : 137.8 kg
- Hard cromed all stages
- All cylinder materials are st 52 cold down tubes
- Standard cylinder is painted with RAL 1036

FORMULATION

- St : (Stroke)
- BL : (Body Length)
- Ro : (Rear Overhang)
- PI : (Pivot Length)
- C : (Bracket Length)

$$\alpha^\circ = \frac{St \times 60}{PI}$$

